

SIZING SCREEN RANGE

522TR

The Maximus 522 Tracked Rinser is the obvious choice for large scale operators who need high capacity and high specification aggregate screening capabilities. The 522TR can be used on its own or as part of an entire wash plant. This makes it one of the most flexible machines available on the market.

FEATURES & BENEFITS

- High energy aggressive 3 deck screen box
- Largest surface area screening capacity 320ft² (29.7m²) on market
- Wedge tensioning system as standard for ease of mesh changes
- Hydraulically driven transfer conveyor eliminates blockages associated with chutes
- Longest conveyors giving maximum stock-piling capacities
- Wide cat walk fully around screenbox which remains fixed for transportation

TECHNICAL SPECIFICATION

WEIGHT	EST 38,000 Kgs (83,790 Lbs)
TRACKS	500mm
POWER UNIT	Cummins 3.8 130 HP Tier 4F
FEEDER CAPACITY	9.2m³
MAIN CONVEYOR	1050mm
SIDE CONVEYOR	800mm
AUXILIARY CONVEYOR	750mm
TRANSFER CONVEYOR	650mm
TOP & MIDDLE DECK	6.700 x 1.525 (22' x 5')
BOTTOM DECK	6.100 x 1.525 (20' x 5')
TRANSPORT LENGTH	18633mm (61'-2")
TRANSPORT HEIGHT	3675mm (12'-1")
TRANSPORT WIDTH	3000mm (9'-10")

SIZING SCREEN RANGE

522TR

